

Technical data sheet

Prime MAGNETIC PET FILM 300

Magnetic PET Film 300 μ is an easy-to-use magnetic polyester based film that can be easily and quickly installed by untrained personnel. It can be applied to almost any steel-based surface to meet the demands for changeable graphics. It is durable and reduces the lifecycle cost for signage.

PRODUCT NAME	Prime Magnetic PET Film 300
PHYSICAL CHARACTERISTICS	
Surface	Satin
Print side	White polyester
Base material	Flexible magnet
Thickness	300 μ
Weight	635 g/m ²
Magnetic holding force	8 - 10 g/m ²
Guaranteed magnetic holding force	\geq 8 g/m ²
Shelf life	1 year under normal conditions*
FEATURES	
Flexible polyester base	
Adheres to steel-based surfaces	
PVC-free	
Indoor and static outdoor use	
Easy to install and remove	
Reduces the life-cycle cost for signage	
Certified for HP Latex inks	
PRINT COMPATIBILITY	
(Eco)Solvent inks	
Latex inks	
UV-cure inks	
Screenprint	

* The shelf life of this media is 1 year under normal conditions (10°C – 35°C at a relative humidity 30% – 75%). Higher humidity and/or temperature can affect the product performance. Always store the media in a dark place in its original packaging.